

## SAFETY DATA SHEET

### Everbuild ShellsolT 250ml

#### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME Everbuild ShellsolT 250ml  
 PRODUCT NO. SA3252  
 SUPPLIER Everbuild Limited  
 Site 41  
 Knowsthorpe Way  
 Cross Green Industrial Estate  
 Leeds LS9 0SW  
 01132 403 456

#### 2 HAZARDS IDENTIFICATION

Repeated exposure may cause skin dryness or cracking. Harmful: may cause lung damage if swallowed.

CLASSIFICATION (1999/45) Xn;R65. R66.

#### 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content %	Classification (67/548/EEC)
ALIPHATIC HYDROCARBON	265-067-2	64741-65-7	60-100%	Xn;R65. R66.

The Full Text for all R-Phrases is Displayed in Section 16

#### 4 FIRST-AID MEASURES

##### INHALATION

Move injured person into fresh air and keep person calm under observation. If uncomfortable: Seek hospital and bring these instructions.

##### INGESTION

DO NOT induce vomiting. Get medical attention immediately.

##### SKIN CONTACT

Remove contaminated clothing immediately and wash skin with soap and water. Prolonged Contact may cause irritation

##### EYE CONTACT

Immediately flush with plenty of water or eyewash solution for up to 10 minutes. Get medical attention if any discomfort continues.

#### 5 FIRE-FIGHTING MEASURES

##### EXTINGUISHING MEDIA

Water spray, dry powder or carbon dioxide.

##### SPECIAL FIRE FIGHTING PROCEDURES

Avoid breathing fire vapours.

##### SPECIFIC HAZARDS

Fire creates: Carbon monoxide (CO).

##### PROTECTIVE MEASURES IN FIRE

Use air-supplied respirator during fire fighting.

#### 6 ACCIDENTAL RELEASE MEASURES

##### PERSONAL PRECAUTIONS

Ensure suitable personal protection (including respiratory protection) during removal of spillages in a confined area.

##### ENVIRONMENTAL PRECAUTIONS

Do not discharge into drains, water courses or onto the ground.

##### SPILL CLEAN UP METHODS

Absorb in vermiculite, dry sand or earth and place into containers.

## Everbuild ShellsoIT 250ml

### 7 HANDLING AND STORAGE

#### USAGE PRECAUTIONS

Avoid contact with skin and eyes. Avoid inhalation of vapours.

#### STORAGE PRECAUTIONS

Store in tightly closed original container in a well-ventilated place.

### 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

#### PROTECTIVE EQUIPMENT



#### PROCESS CONDITIONS

Provide eyewash station.

#### ENGINEERING MEASURES

Provide adequate ventilation. Observe Occupational Exposure Limits and minimise the risk of inhalation of vapours.

#### RESPIRATORY EQUIPMENT

In case of brief exposure use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.

#### HAND PROTECTION

Use suitable protective gloves if risk of skin contact.

#### EYE PROTECTION

Wear splash-proof eye goggles to prevent any possibility of eye contact.

#### HYGIENE MEASURES

Wash at the end of each work shift and before eating, smoking and using the toilet.

#### SKIN PROTECTION

Wear apron or protective clothing in case of splashes.

### 9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid
COLOUR	Colourless
ODOUR	Mild
SOLUBILITY	Immiscible with water
BOILING POINT (°C)	184
MELTING POINT (°C)	>-70
RELATIVE DENSITY	.761
VAPOUR PRESSURE	1.1 kPa
FLASH POINT (°C)	61
AUTO IGNITION	354
TEMPERATURE (°C)	
VOLATILE ORGANIC COMPOUND (VOC)	100%

### 10 STABILITY AND REACTIVITY

#### STABILITY

Stable under normal temperature conditions and recommended use.

### 11 TOXICOLOGICAL INFORMATION

Name ALIPHATIC HYDROCARBON

## Everbuild ShellsoIT 250ml

**12 ECOLOGICAL INFORMATION**

Name ALIPHATIC HYDROCARBON

**13 DISPOSAL CONSIDERATIONS**

## DISPOSAL METHODS

Arrange disposal with a licensed waste disposal company.

**14 TRANSPORT INFORMATION**

PROPER SHIPPING NAME	Hydrocarbons Liquid, N.O.S.
ENVIRONMENTALLY HAZARDOUS SUBSTANCE/MARINE POLLUTANT	No.
UN NO. ROAD	3295
ADR CLASS NO.	3
ADR CLASS	Class 3: Flammable liquids.
ADR PACK GROUP	III
HAZARD NO. (ADR)	30 Flammable liquid (flash-point between 23°C and 60°C, inclusive) or flammable liquid or solid in the molten state with a flash-point above 60°C, heated to a temperature equal to or above its flash-point, or self heating liquid.
UN NO. SEA	3295
IMDG CLASS	3
EMS	F-E, S-E
UN NO. AIR	3295
AIR CLASS	3
AIR PACK GR.	III

**15 REGULATORY INFORMATION**

## LABELLING



Harmful

CONTAINS ALIPHATIC HYDROCARBON

## RISK PHRASES

R65 Harmful: may cause lung damage if swallowed.  
 R66 Repeated exposure may cause skin dryness or cracking.

**Everbuild ShellsoIT 250ml**

## SAFETY PHRASES

S37	Wear suitable gloves.
S60	This material and its container must be disposed of as hazardous waste.
S62	If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

**16 OTHER INFORMATION**

DATE 22 September 2011

## RISK PHRASES IN FULL

R65 Harmful: may cause lung damage if swallowed.  
R66 Repeated exposure may cause skin dryness or cracking.